



FRONTEQ electric powered aerial work platforms feature higher productivity, longer run time and greater uptime.

SPECIFICATION

Self-propelled Scissor Lifts

MODEL	WORKING HEIGHT		WIDTH		TURNING RADIUS*		LIFT CAPACITY		GRADEABILITY**	
	MEASUREMENT	US	METRIC	US	METRIC	US	METRIC	US		METRIC
FS0407		21 ft 4 in	6.5 m	2 ft 6 in	0.76 m	0	0	617 lb	280 kg	30%
FS0407W		21 ft 4 in	6.5 m	2 ft 8 in	0.81 m	0	0	617 lb	280 kg	30%
FS0407E		19 ft	5.8 m	2 ft 6 in	0.76 m	2 in	0.04 m	507 lb	230 kg	25%
FS0507E		22 ft 4 in	6.8 m	2 ft 8 in	0.81 m	2 in	0.04 m	507 lb	230 kg	25%
FS0607		25 ft 7 in	7.8 m	2 ft 6 in	0.76 m	0	0	507 lb	230 kg	25%
FS0607W		25 ft 7 in	7.8 m	2 ft 8 in	0.81 m	0	0	507 lb	230 kg	25%
FS0612		26 ft 3 in	8.0 m	3 ft 10 in	1.18 m	0	0	1212 lb	550 kg	30%
FS0808		32ft 6 in	9.9 m	2 ft 8 in	0.81 m	0	0	507 lb	230 kg	25%
FS0812		32 ft 6 in	9.9 m	3 ft 10 in	1.18 m	0	0	1014 lb	460 kg	30%
FS1012		38 ft 9 in	11.8 m	3 ft 10 in	1.18 m	0	0	705 lb	320 kg	25%
FS1012E		38 ft 9 in	11.8 m	3 ft 10 in	1.18 m	0	0	705 lb	320 kg	30%
FS1212		45 ft 3 in	13.8 m	3 ft 10 in	1.18 m	0	0	705 lb	320 kg	25%
FS1212E		45 ft 3 in	13.8 m	3 ft 10 in	1.18 m	0	0	705 lb	320 kg	30%
FS1414		51 ft 10 in	15.8 m	4 ft 7 in	1.40 m	0	0	661 lb	300 kg	30%
FS1414E		51 ft 10 in	15.8 m	4 ft 7 in	1.40 m	0	0	661 lb	300 kg	30%
FS0507T		21 ft 8 in	6.6 m	2 ft 7 in	0.8 m	0	0	441 lb	200 kg	30%

* Inside Radius

**Gradeability applies to driving on slopes, see operation manual for details regarding slope ratings. Gradeability may vary depending on options installed on equipment.

